Tubo GOMMA

Può essere impiegato in una gamma di temperature variante da -30°C a +60°C. Tubo per mandata d'acqua industriale, aria e fluidi non corrosivi. Sottostrato nero liscio in elastomero Tiprene con ottime caratteristiche meccaniche e bassa permeabilità all'aria, rete di fili in poliestere ad alta tenacità, copertura in elastomero Tiprene resistente all'abrasione e all'invecchiamento. Superficie esterna nera liscia.

RUBBER hose

It can be used at a temperature range varying from -30°C to +60°C. Suitable for flow of industrial water, air and non-corrosive fluids. Black smooth substrate of TIPRENE elastomer, with excellent mechanical features and low permeability to air, braid of highly tough TIPRENE elastomer, overlay in TIPRENE elastomer resistant to abrasion and aging. Black smooth external surface.



Art.	Ø esterno *outside Ø*	Ø interno *inside Ø*	Pressione scoppio *Bursting pressure*	Pressione esercizio *Working pressure*	Colore *Colour*	Rotoli mt. *Rolls mt.*	€
TG/1	14	6	60	20	Nero • *Black*	100	
TG/2	17	8	60	20	Nero • *Black*	100	
TG/4	19	10	60	20	Nero • *Black*	100	
TG/5	23	13	60	20	Nero • *Black*	100	
TG/7	26	16	60	20	Nero • *Black*	100	
TG/8	30	19	60	20	Nero • *Black*	50	
TG/9	37	25	60	20	Nero • *Black*	50	

Tubo GOMMA

Può essere impiegato in una gamma di temperature variante da -20°C a +60°C. Tubo per mandata d'acqua industriale, aria e fluidi non corrosivi. Sottostrato nero liscio in elastomero Tiprene con ottime caratteristiche meccaniche e bassa permeabilità all'aria, rete di fili in poliestere ad alta tenacità, copertura in elastomero Tiprene resistente all'abrasione e all'invecchiamento. Superficie esterna nera liscia.

RUBBER hose

It can be used at a temperature range varying from -20°C to +60°C. Suitable for flow of industrial water, air and non-corrosive fluids. Black smooth substrate of TIPRENE elastomer, with excellent mechanical features and low permeability to air, braid of highly tough TIPRENE elastomer, overlay in TIPRENE elastomer resistant to abrasion and aging. Black smooth external surface.



Art.	Ø esterno *outside Ø*	Ø interno *inside Ø*	Pressione scoppio *Bursting pressure*	Pressione esercizio *Working pressure*	Colore *Colour*	Rotoli mt. *Rolls mt.*	€
TG/0/10	10.5	5	30	10	Nero • *Black*	100	
TG/1/10	15	8	30	10	Nero • *Black*	100	
TG/2/10	17	10	30	10	Nero • *Black*	100	
TG/3/10	17	12	30	10	Nero • *Black*	100	
TG/4/10	19	13	30	10	Nero • *Black*	100	
TG/5/10	21	15	30	10	Nero • *Black*	100	
TG/6/10	23	16	30	10	Nero • *Black*	100	
TG/7/10	26	19	30	10	Nero • *Black*	100	
TG/8/10	30	20	30	10	Nero • *Black*	50	
TG/9/10	30	22	30	10	Nero • *Black*	50	
TG/10/10	35	25	30	10	Nero • *Black*	50	