TUBI PLASTICI

Tubo flessibile RILSAN PA12 PHL

Può essere impiegato in una gamma di temperature variante da -40°C a +70°C. Il tubo soddisfa i requisiti della norma DIN 73378. A richiesta colore: blu, giallo, rosso, verde, nero (il prezzo può variare)

PA12 PHL hose

It can be used at a temperature range varying from -40°C to +70°C. This hose complies with the requirements of the law DIN 73378 . On request colour: blue, yellow, red, green, black (the price can change)



Art.	Ø esterno *outside Ø*	Ø interno *inside Ø*	Pressione scoppio *Bursting pressure*	Pressione esercizio *Working pressure*	Colore *Colour*	Rotoli mt. *Rolls mt.*	€
RFL/3	4	2	126	42	neutro • *natural*	100	
RFL/4	4	2,5	92	30	neutro • *natural*	100	
RFL/6	5	3	96	32	neutro • *natural*	100	
RFL/7	6	4	76	25	neutro • *natural*	100	
RFL/8	8	6	56	18	neutro • *natural*	100	
RFL/8A	10	7	71	24	neutro • *natural*	100	
RFL/10	10	8	42	14	neutro • *natural*	100	
RFL/11	12	8	72	24	neutro • *natural*	100	
RFL/12	12	10	36	12	neutro • *natural*	100	
RFL/13	14	12	33	11	neutro • *natural*	100	
RFL/14	15	12,5	36	12	neutro • *natural*	50	
RFL/13A	16	12	57	19	neutro • *natural*	50	
RFL/15	16	14	30	10	neutro • *natural*	50	

Tubo flessibile RILSAN PA11 PHL

Può essere impiegato in una gamma di temperature variante da -40°C a +80°C. Il tubo soddisfa i requisiti della norma DIN 74324. A richiesta colore: blu, giallo, rosso, verde, nero (il prezzo può variare)

RILSAN PA11 PHL hose

It can be used at a temperature range varying from -40°C to +80°C. This hose complies with the requirements of the law DIN 74324 . On request colour: blue, yellow, red, green, black (the price can change)



Art.	Ø esterno *outside Ø*	Ø interno *inside Ø*	Pressione scoppio *Bursting pressure*	Pressione esercizio *Working pressure*	Colore *Colour*	Rotoli mt. *Rolls mt.*	€
FL/1	2	1	133	44	neutro • *natural*	100	
FL/2	3	2	80	27	neutro • *natural*	100	
FL/3	4	2	132	44	neutro • *natural*	100	
FL/4	4	2,5	106	32	neutro • *natural*	100	
FL/5	4	2,7	78	26	neutro • *natural*	100	
FL/6	5	3	100	33	neutro • *natural*	100	
FL/7	6	4	84	28	neutro • *natural*	100	
FL/8	8	6	60	20	neutro • *natural*	100	
FL/10	10	8	45	15	neutro • *natural*	100	
FL/11	12	8	78	28	neutro • *natural*	100	
FL/12	12	10	39	13	neutro • *natural*	100	
FL/13	14	12	31	10	neutro • *natural*	100	
FL/14	15	12,5	36	12	neutro • *natural*	50	
FL/12A	16	13	41	14	neutro • *natural*	100	
FL/15	16	14	27	9	neutro • *natural*	50	
FL/16	18	15	36	12	neutro • *natural*	50	
FL/17	20	18	21	7	neutro • *natural*	50	
FL/21	30	25	36	12	neutro • *natural*	25	

Tubo PA12 Autoestinguente

Impiegato in una gamma di temperature variante da -30°C a +70°C. Idoneo per impianti aria. Caratteristiche: prodotto senza alogeni - autoestinguente secondo norma UL 94/V2.

Self-extinguishing PA12 hose

It can be used at a temperature range varying from -30°C to +70°C. Suitable for air systems. Features : halogen-free product, self-extinguishing according to law UL 94/V2.



PA12 autoestinguente

Art.	Ø esterno *outside Ø*	Ø interno *inside Ø*	Pressione scoppio *Bursting pressure*	Pressione esercizio *Working pressure*	Colore *Colour*	Rotoli mt. *Rolls mt.*	€
RA/0	6	4	88	29	Blu	100	
RA/1	8	6	80	26	Blu	100	
RA/2	10	8	60	20	Blu	100	
RA/3	12	10	40	13	Blu	100	
RA/4	15	12	49	16	Blu	50	
RA/5	18	15	52	17	Blu	50 mt ± 20%	
RA/6	22	18	44	15	Blu	50 mt ± 20%	
RA/7	24	20	40	13	Blu	50 mt ± 20%	
RA/7A	28	24	34	11	Blu	50 mt ± 20%	
RA/8	40	34	36	12	Blu	50 mt ± 20%	

Tubo RILSAN® HT Alte temperature

Tubo in Bio-Polimero poliftalammide (PPA) termoplastico RILSAN® HT ottenuta da fonti rinnovabili • Bio-polimero semi-flessibile stabilizzato alla luce e al calore idoneo per utilizzo a temperature elevate. Temperature da -30°C a +150°C.

RILSAN® HT High-temperature hose

Bio-Polymer Poliftalammide (PPA) RILSAN® HT thermoplastic tubing obtained from renewable sources • Semi-flexible bio-polymer stabilized to light and heat, suitable for usage at high temperatures. Temperature range from -30°C to +150°C.



Rilsan HT

Art.	Ø esterno *outside Ø*	Ø interno *inside Ø*	Pressione scoppio *Bursting pressure*	Pressione esercizio *Working pressure*	Colore *Colour*	Rotoli mt. *Rolls mt.*	€
HFL/7 NERO	6	4	120	40	Nero • *Black*	50	
HFL/8 NERO	8	6	85	28	Nero • *Black*	50	
HFL/10 NERO	10	8	66	22,00	Nero • *Black*	50	
HFL/12 NERO	12	10	54	18,00	Nero • *Black*	50	

Tubo PTFE

Può essere impiegato in una gamma di temperature variante da -60°C a +260°C. Idoneo nel settore alimentare e in ambienti di lavoro aggressivi. Ottima resistenza ai prodotti chimici e agli agenti atmosferici.

PTFE hose

It can be used at a temperature range varying from -60°C to +260°C. Suitable for food industry and aggressive workplaces. Excellent resistance to chemical products and weather conditions.



PTFE

Art.	Ø esterno *outside Ø*	Ø interno *inside Ø*	Pressione scoppio *Bursting pressure*	Pressione esercizio *Working pressure*	Colore *Colour*	Rotoli mt. *Rolls mt.*	€
TE/1	4	2	60	20	neutro • *natural*	50	
TE/3	6	4	40	13	neutro • *natural*	50	
TE/5	8	6	30	10	neutro • *natural*	50	
TE/6	10	8	24	8	neutro • *natural*	50	
TE/7	12	10	20	7	neutro • *natural*	50	

Tubo flessibile RILSAN PA11 PHL

Confezione da 25 mt. di Tubo flessibile PA11 PHL - DIN 74324.

Caratteristiche: le stesse della gamma FL

RILSAN PA11 PHL hose

25 mt. packs PA11 PHL - DIN 74324 flexible hoses.

Features : the same as FL range.



PA11

Art.	Ø esterno *outside Ø*	Ø interno *inside Ø*	Pressione scoppio *Bursting pressure*	Pressione esercizio *Working pressure*	Colore *Colour*	Rotoli mt. *Rolls mt.*	€ / pc
25SC-PA1124	4	2	132	44	neutro ▪ *natural*	25	
25SC-PA11254	4	2,5	106	32	neutro ▪ *natural*	25	
25SC-PA1146	6	4	84	28	neutro ▪ *natural*	25	
25SC-PA1168	8	6	60	20	neutro ▪ *natural*	25	
25SC-PA11810	10	8	45	15	neutro ▪ *natural*	25	
25SC-PA111012	12	10	39	13	neutro ▪ *natural*	25	
25SC-PA111214	14	12	31	10	neutro ▪ *natural*	25	

Tubo flessibile RILSAN PA12 PHL

Confezione da 25 mt. di Tubo flessibile PA12 PHL - DIN 73378.

Caratteristiche: le stesse della gamma RFL

PA12 PHL hose

25 mt. packs PA12 PHL - DIN 73378 flexible hoses.

Features : the same as FL range.



PA12

Art.	Ø esterno *outside Ø*	Ø interno *inside Ø*	Pressione scoppio *Bursting pressure*	Pressione esercizio *Working pressure*	Colore *Colour*	Rotoli mt. *Rolls mt.*	€ / pc
25SC-PA24X25	4	2	126	42	neutro ▪ *natural*	25	
25SC-PA274X25	4	2,7	78	26	neutro ▪ *natural*	25	
25SC-PA46X25	6	4	76	25	neutro ▪ *natural*	25	
25SC-PA68X25	8	6	56	18	neutro ▪ *natural*	25	
25SC-PA810X25	10	8	42	14	neutro ▪ *natural*	25	
25SC-PA1012X25	12	10	36	12	neutro ▪ *natural*	25	
25SC-PA1214X25	14	12	33	11	neutro ▪ *natural*	25	

Tubo calibrato POLIURETANO 98 ShA

Confezione da 25 mt. di Tubo calibrato in POLIURETANO 98 ShA.

Caratteristiche: le stesse della gamma RFL

Calibrated hoses POLYURETHANE 98 ShA

25 mt. packs POLYURETHANE 98 ShA .

Features : the same as FL range.



PU 98 ShA

Art.	Ø esterno *outside Ø*	Ø interno *inside Ø*	Pressione scoppio *Bursting pressure*	Pressione esercizio *Working pressure*	Colore *Colour*	Rotoli mt. *Rolls mt.*	€ / pc
25SC-PU25425B	4	2,5	40	10	Blu	25	
25SC-PU3525B	5	3	50	12	Blu	25	
25SC-PU4625B	6	4	40	10	Blu	25	
25SC-PU5825B	8	5	52	13	Blu	25	
25SC-PU55825B	8	5,5	40	10	Blu	25	
25SC-PU6825B	8	6	28	7	Blu	25	
25SC-PU651025B	10	6,5	40	10	Blu	25	
25SC-PU91225B	12	9	25	6	Blu	25	
25SC-PU101425B	14	10	27	9	Blu	25	

Tubo POLIETILENE BASSA DENSITÁ

Può essere impiegato in una gamma di temperature da -10°C a +60°C. Idoneo per uso pneumatico. A richiesta colore : blu, giallo, rosso, verde, nero (il prezzo può variare)



LOW-DENSITY POLYETHYLENE hose

It can be used at a temperature range varying from -10°C to +60°C. Suitable for pneumatics. On request colour: blu, yellow, red, green, black (the price can change)

Art.	Ø esterno *outside Ø*	Ø interno *inside Ø*	Pressione scoppio *Bursting pressure*	Pressione esercizio *Working pressure*	Colore *Colour*	Rotoli mt. *Rolls mt.*	€
PE/1	4	2	63	21,0	neutro ▪ *natural*	100	
PE/2	4	2,5	44	15	neutro ▪ *natural*	100	
PE/4	5	3	48	16	neutro ▪ *natural*	100	
PE/5	6	4	38	13	neutro ▪ *natural*	100	
PE/6	8	6	27	9	neutro ▪ *natural*	100	
PE/5A	10	7	34	11	neutro ▪ *natural*	100	
PE/8	10	8	21	7	neutro ▪ *natural*	100	
PE/8A	12	9	27	9	neutro ▪ *natural*	100	
PE/9	12	10	17	6	neutro ▪ *natural*	100	
PE/10	15	12,5	17	6	neutro ▪ *natural*	100	

Tubo SILICONE

Tubo alimentare per distributori di bevande o macchine per caffè. Tubo trasporto vapore a bassa pressione. Colore disponibile: solo neutro.



SILICON hose

Food quality hose for drink dispensers and coffee machines. Hose for steam passage at low pressure. Only colour available: natural.

Art.	Ø esterno *outside Ø*	Ø interno *inside Ø*	Pressione scoppio *Bursting pressure*	Peso gr. *Weight gr.*	Colore *Colour*	Rotoli mt. *Rolls mt.*	€
SA/1	7	4	-	33	neutro ▪ *natural*	100	
SA/1A	9	5	-	55	neutro ▪ *natural*	100	
SA/2	10	6	-	63	neutro ▪ *natural*	100	
SA/3	11	7	-	71	neutro ▪ *natural*	100	
SA/4	12	8	-	80	neutro ▪ *natural*	50	
SA/6	14	10	-	95	neutro ▪ *natural*	50	

Tubo POLIETILENE ALIMENTARE

Può essere impiegato in una gamma di temperature da -10°C a +60°C. A richiesta colore : nero, blu, rosso (il prezzo può variare)



POLYETHYLENE hose for FOOD INDUSTRY

It can be used at a temperature range varying from -10°C to +60°C. On request colour: black, blue, red (the price can change)

Art.	Ø esterno *outside Ø*	Ø interno *inside Ø*	Pressione scoppio *Bursting pressure*	Pressione esercizio *Working pressure*	Colore *Colour*	Rotoli mt. *Rolls mt.*	€
PEA/2 NEUTRO	4	2,5	44	15	neutro ▪ *natural*	100	
PEA/5 NEUTRO	6	4	38	13	neutro ▪ *natural*	100	
PEA/6 NEUTRO	8	6	27	9	neutro ▪ *natural*	100	
PEA/5A NEUTRO	10	7	34	11	neutro ▪ *natural*	100	
PEA/8 NEUTRO	10	8	21	7	neutro ▪ *natural*	100	
PEA/9 NEUTRO	10	12	17	6	neutro ▪ *natural*	100	
PEA/8A NEUTRO	12	9	27	9	neutro ▪ *natural*	100	
PEA/10 NEUTRO	15	12,5	17	6	neutro ▪ *natural*	100	

Tubo NYLON PA6

Può essere impiegato in una gamma di temperature da -10°C a +80°C. . Idoneo per il passaggio di olio e grasso a bassa pressione. A richiesta colore : azzurro, giallo, rosso, verde, nero (il prezzo può variare)

NYLON PA6 hose

It can be used at a temperature range varying from -10°C to +80°C. Suitable for conveying low-pressure oil and grease. On request colour: light blue, yellow, red, green, black (the price can change)



PA6

Art.	Ø esterno *outside Ø*	Ø interno *inside Ø*	Pressione scoppio *Bursting pressure*	Pressione esercizio *Working pressure*	Colore *Colour*	Rotoli mt. *Rolls mt.*	€
SR/0A	3	2	100	33	neutro ▪ *natural*	100	
SR/1	4	2	167	56	neutro ▪ *natural*	100	
SR/2	4	2,5	115	38	neutro ▪ *natural*	100	
SR/3	4	3	71	24	neutro ▪ *natural*	100	
SR/4	5	3	125	42	neutro ▪ *natural*	100	
SR/5	6	4	100	33	neutro ▪ *natural*	100	
SR/6	8	6	71	24	neutro ▪ *natural*	100	
SR/8	10	8	56	19	neutro ▪ *natural*	100	
SR/9	12	8	100	33	neutro ▪ *natural*	100	
SR/10	12	10	45	15	neutro ▪ *natural*	100	
SR/11	14	12	38	13	neutro ▪ *natural*	100	
SR/12	15	12,5	45	15	neutro ▪ *natural*	100	
SR/13	16	14	33	11	neutro ▪ *natural*	50	
SR/15	18	16	29	10	neutro ▪ *natural*	50	

MULTITUBO PU TERMOSALDATO

Colore standard: azzurro e nero

THERMO-WELDED PU MULTIHOSE

Standard colour: blue and black



Art.	Ø esterno *outside Ø*	Ø interno *inside Ø*	Pressione scoppio *Bursting pressure*	Pressione esercizio *Working pressure*	N° tubi *N° of hoses*	Rotoli mt. *Rolls mt.*	€
908/1	4	2,5	40	10	2	100	
908/2	6	4	40	10	2	100	
908/3	8	5,5	40	10	2	100	
908/4	8	6	28	7	2	100	
908/5	10	6,5	40	10	2	100	
908/6	10	8	27	7	2	100	

Tubo TELATO

LINEN hose



Art.	Ø esterno *outside Ø*	Ø interno *inside Ø*	Pressione scoppio *Bursting pressure*	Pressione esercizio *Working pressure*	Colore *Colour*	Rotoli mt. *Rolls mt.*	€
TT/1	6	4	40	16	Blu	50	
TT/2	8	6	35	11	Blu	50	
TT/3	10	8	30	10	Blu	50	
TT/4	12	10	27	9	Blu	50	
TT/5	15	12,5	24	8	Blu	50	