# RACCORDERIA PER ARIA COMPRESSA IN OTTONE GIALLO OT.58
# YELLOW BRASS OT.58 COUPLINGS AND FITTINGS FOR COMPRESSED AIR

| | | |
|---|---|---|
| Tassi nominali di flusso secondo ISO 6358 | | 1.500 NL/min |
| Nominal flow rates acc.to ISO 6358 | | 1.500 NL/min |
| Fluido di passaggio Flow medium | | aria compressa pre-filtrata a 40 µm 40 µm pre-filtered compressed air |
| Pressione massima di esercizio Max. operating pressure | | 16 bar |
| Gamma di temperatura Temperature range | | -15°C fino a +80°C -15°C up to +80°C |
| Materiali Materials | rubinetto: ottone | molle: acciaio per molle |
| | coupling: brass | springs: spring steel |
| | guarnizione: NBR | rulli: acciaio inox |
| | gasket: NBR | rolls: stainless steel |



Compatibile con:
Compatible with:




Intercambiabile con profilo• Interchangeable with profiles:
Rectus 26 - Rectus 25 - Rectus 1600 - Rectus 1625 - Cejn 320 - Jwl 520 - Jwl 530

| | Art. | Size • Ø | € |
|---|---|---|---|
| Maschio Male | 500/M1 | 1/4" | |
| | 500/M2 | 3/8" | |
| | 500/M3 | 1/2" | |
| Femmina Female | 500/F1 | 1/4" | |
| | 500/F2 | 3/8" | |
| | 500/F3 | 1/2" | |
| Attacco portagomma With hose tail fitting | 500/P1 | 6 | |
| | 500/P2 | 9 | |
| | 500/P3 | 13 | |
| Maschio Male | 501/M1 | 1/4" | |
| | 501/M2 | 3/8" | |
| | 501/M3 | 1/2" | |
| Femmina Female | 501/F1 | 1/4" | |
| | 501/F2 | 3/8" | |
| | 501/F3 | 1/2" | |
| Attacco portagomma Hose tail fitting | 501/P1 | 6 | |
| | 501/P2 | 9 | |
| | 501/P3 | 13 | |
| Distributore a 2 rubinetti Distributor with 2 couplings | 502/V2 | 3/8" | |
| | | 3/8" | |
| | 502/V2 SR | senza rubinetti without couplings | |
| Distributore a 3 rubinetti Distributor with 3 couplings | 502/V3 | 3/8" | |
| | | 3/8" | |
| | 502/V3 SR | senza rubinetti without couplings | |

| | Art. | Size • Ø | | € |
|---|---|---|---|---|
| Nipplo cilindrico Parallel nipple | 504/0 | 1/4" | 1/8" | |
| | 504/1 | 1/4" | 1/4" | |
| | 504/2 | 3/8" | 1/4" | |
| | 504/3 | 3/8" | 3/8" | |
| | 504/4 | 1/2" | 1/4" | |
| | 504/5 | 1/2" | 3/8" | |
| | 504/6 | 1/2" | 1/2" | |
| Riduzione cilindrica M.F. Parallel reduction | 505/1 | 1/8" | 1/4" | |
| | 505/2 | 1/4" | 3/8" | |
| | 505/3 | 3/8" | 1/2" | |
| Riduzione cilindrica M.F. Parallel reduction | 506/1 | 1/4" | 1/8" | |
| | 506/2 | 3/8" | 1/4" | |
| | 506/3 | 1/2" | 1/4" | |
| | 506/4 | 1/2" | 3/8" | |
| | 506/5 | 3/4" | 1/2" | |
| Attacco portagomma cilindrico Rubber hose tail fitting parallel male thread | 507/1 | 1/4" | 6 | |
| | 507/2 | 1/4" | 9 | |
| | 507/3 | 3/8" | 6 | |
| | 507/4 | 3/8" | 9 | |
| | 507/5 | 3/8" | 13 | |
| Attacco femmina portagomma Female rubber hose tail fitting | 508/1 | 1/4" | 6 | |
| | 508/2 | 1/4" | 9 | |
| | 508/3 | 3/8" | 6 | |
| | 508/4 | 3/8" | 9 | |
| Attacco doppio tubo Double hose tail fitting | 100/FF2 | 6 | | |
| | 100/FF3A | 9 | | |
| | 100/FF6 | 13 | | |
| | 509/1 | 6 | | |
| | 509/2 | 9 | | |