PRESSOSTATI PER COMPRESSORI ARIA
PRESSURE SWITCHES FOR AIR COMPRESSORS

Authorized

A richiesta forniamo anche modelli diversi • *On request we supply also different models*

	Ref.	**Modello** ***Model***	Pressione massima *Max pressure*	Taratura di fabbrica *Factory pressure adjustment*	Flangia *Flange*	Versione *Version*	Valvola di scarico *Unloader valve*	Pressacavi *Cable glands*	Protezione termica *Overload relay*	Altre caratteristiche *Other details*	€
						CONDOR					
	127/1C	**MDR 1** ***single phase***	11 bar	Pre-tarato a 6-8 bar *Pre-adjusted at 6-8 bar*	G.1/4" 1 VIA *G.1/4" 1-WAY*	Standard EURO con terminali a vite *EURO-Standard with screw terminals*	AEV S ritardata attacco rapido 6mm *AEV S delayed quick connect 6mm*	PG 11 Z con gommino + PG 11 ZK con gommino e supporto cavo *PG 11 Z with strain relief + PG 11 ZK with strain relief and cable support*	Senza termica *Without overload relay*	Diaframma standard, pulsante ON/OFF *Standard diaphragm, ON-OFF manual switch*	
	127/2CA	**MDR 1** ***single phase***	11 bar	Pre-tarato a 7-9 bar *Pre-adjusted at 7-9 bar*	G.1/4" 4 VIE *G.1/4" 4-WAY*	Standard EURO con terminali a vite *EURO-Standard with screw terminals*	AEV S ritardata attacco rapido 6mm *AEV S delayed quick connect 6mm*	PG 11 Z con gommino + PG 11 ZK con gommino e supporto cavo *PG 11 Z with strain relief + PG 11 ZK with strain relief and cable support*	Senza termica *Without overload relay*	Diaframma standard, pulsante ON/OFF *Standard diaphragm, ON-OFF manual switch*	
	127/6C	**MDR 1** ***single phase***	11 bar	Pre-tarato a 6-8 bar *Pre-adjusted at 6-8 bar*	G.1/4" 4 VIE *G.1/4" 4-WAY*	Standard EURO con terminali a vite *EURO-Standard with screw terminals*	EV S attacco rapido 6mm *EV S quick connect 6mm*	PG 11 Z con gommino + PG 11 ZK con gommino e supporto cavo *PG 11 Z with strain relief + PG 11 ZK with strain relief and cable support*	Senza termica *Without overload relay*	Diaframma standard, pulsante ON/OFF *Standard diaphragm, ON-OFF manual switch*	
	127/2C	**MDR 2** ***single phase***	11 bar	Pre-tarato a 6-8 bar *Pre-adjusted at 6-8 bar*	G.1/4" 1 VIA *G.1/4" 1-WAY*	Standard EURO con terminali a vite, senza differenziale *EURO-Standard with screw terminals, without pressure differential*	EV S attacco rapido 6mm *EV S quick connect 6mm*	PG 11 ZK con gommino e supporto cavo + PG 11 Z con gommino *PG 11 ZK with strain relief and cable support + PG 11 Z with strain relief*	Senza termica *Without overload relay*	Diaframma standard, pulsante ON/OFF *Standard diaphragm, ON-OFF manual switch*	
	127/2CB	**MDR 2** ***single phase***	11 bar	Pre-tarato a 6-8 bar *Pre-adjusted at 6-8 bar*	G.1/4" 4 VIE *G.1/4" 4-WAY*	Standard EURO con terminali a vite, senza differenziale *EURO-Standard with screw terminals, without pressure differential*	EV S attacco rapido 6mm *EV S quick connect 6mm*	PG 11 ZK con gommino e supporto cavo + PG 11 Z con gommino *PG 11 ZK with strain relief and cable support + PG 11 Z with strain relief*	Senza termica *Without overload relay*	Diaframma standard, pulsante ON/OFF *Standard diaphragm, ON-OFF manual switch*	
	127/3C	**MDR 4** ***3-phase***	11 bar	Pre-tarato a 9-11 bar *Pre-adjusted at 9-11 bar*	G.1/4" 1 VIA *G.1/4" 1-WAY*	Ampio spazio per il cablaggio *Large wiring space*	EV raccordo vite 6mm *EV screw fitting 6mm*	PG 11 ZK con gommino e supporto cavo + PG 11 Z con gommino *PG 11 ZK with strain relief and cable support + PG 11 Z with strain relief*	Senza termica *Without overload relay*	Diaframma standard, pulsante ON/OFF *Standard diaphragm, ON-OFF manual switch*	
	127/3CA	**MDR 4** ***3-phase***	11 bar	Pre-tarato a 9-11 bar *Pre-adjusted at 9-11 bar*	G.1/4" 4 VIE *G.1/4" 4-WAY*	Ampio spazio per il cablaggio *Large wiring space*	EV raccordo vite 6mm *EV screw fitting 6mm*	PG 11 ZK con gommino e supporto cavo + PG 11 Z con gommino *PG 11 ZK with strain relief and cable support + PG 11 Z with strain relief*	Senza termica *Without overload relay*	Diaframma standard, pulsante ON/OFF *Standard diaphragm, ON-OFF manual switch*	

PRESSOSTATI PER COMPRESSORI ARIA
PRESSURE SWITCHES FOR AIR COMPRESSORS

Authorized

A richiesta forniamo anche modelli diversi • *On request we supply also different models*

	Ref.	**Modello** ***Model***	Pressione massima *Max pressure*	Taratura di fabbrica *Factory pressure adjustment*	Flangia *Flange*	Versione *Version*	Valvola di scarico *Unloader valve*	Pressacavi *Cable glands*	Protezione termica *Overload relay*	Altre caratteristiche *Other details*	€
	CONDOR										
	127/4CT 4-6,3	**MDR 3** ***3-phase***	11 bar	Pre-tarato a 9-11 bar *Pre-adjusted at 9-11 bar*	G.1/4" 1 VIA *G.1/4" 1-WAY*	Standard EURO con terminali a vite *EURO-Standard with screw terminals*	EV S attacco rapido 6mm *EV S quick connect 6mm*	PG 13,5 Z con gommino + PG 13,5 ZK con gommino e supporto cavo *PG 13.5 Z with strain relief + PG 13.5 ZK with strain relief and cable support*	Termica 4,0-6,3 A *Overload relay 4.0-6.3 A*	Diaframma standard, pulsante ON/OFF *Standard diaphragm, ON-OFF manual switch*	
	127/4CT 6-10	**MDR 3** ***3-phase***	11 bar	Pre-tarato a 7-9 bar *Pre-adjusted at 7-9 bar*	G.1/4" 1 VIA *G.1/4" 1-WAY*	Standard EURO con terminali a vite *EURO-Standard with screw terminals*	EV S attacco rapido 6mm *EV S quick connect 6mm*	PG 13,5 Z con gommino + PG 13,5 ZK con gommino e supporto cavo *PG 13.5 Z with strain relief + PG 13.5 ZK with strain relief and cable support*	Termica 6,3-10 A *Overload relay 6.3-10 A*	Diaframma standard, pulsante ON/OFF *Standard diaphragm, ON-OFF manual switch*	
	127/4CT 10-16	**MDR 3** ***3-phase***	11 bar	Pre-tarato a 7-9 bar *Pre-adjusted at 7-9 bar*	G.1/4" 1 VIA *G.1/4" 1-WAY*	Standard EURO con terminali a vite *EURO-Standard with screw terminals*	EV S attacco rapido 6mm *EV S quick connect 6mm*	PG 13,5 Z con gommino + PG 13,5 ZK con gommino e supporto cavo *PG 13.5 Z with strain relief + PG 13.5 ZK with strain relief and cable support*	Termica 10,0-16,0 A *Overload relay 10.0-16.0 A*	Diaframma standard, pulsante ON/OFF *Standard diaphragm, ON-OFF manual switch*	
	127/4CT 16-20	**MDR 3** ***3-phase***	11 bar	Pre-tarato a 7-9 bar *Pre-adjusted at 7-9 bar*	G.1/4" 1 VIA *G.1/4" 1-WAY*	Standard EURO con terminali a vite *EURO-Standard with screw terminals*	EV S attacco rapido 6mm *EV S quick connect 6mm*	PG 13,5 Z con gommino + PG 13,5 ZK con gommino e supporto cavo *PG 13.5 Z with strain relief + PG 13.5 ZK with strain relief and cable support*	Termica 16,0-20,0 A *Overload relay 16.0-20.0 A*	Diaframma standard, pulsante ON/OFF *Standard diaphragm, ON-OFF manual switch*	
	127/5CT 4-6,3	**MDR 3** ***3-phase***	11 bar	Pre-tarato a 7-9 bar *Pre-adjusted at 7-9 bar*	G.1/4" 4 VIE *G.1/4" 4-WAY*	Standard EURO con terminali a vite *EURO-Standard with screw terminals*	EV S attacco rapido 6mm *EV S quick connect 6mm*	PG 13,5 Z con gommino + PG 13,5 ZK con gommino e supporto cavo *PG 13.5 Z with strain relief + PG 13.5 ZK with strain relief and cable support*	Termica 4,0-6,3 A *Overload relay 4.0-6.3 A*	Diaframma standard, pulsante ON/OFF *Standard diaphragm, ON-OFF manual switch*	
	127/5CT 6-10	**MDR 3** ***3-phase***	11 bar	Pre-tarato a 7-9 bar *Pre-adjusted at 7-9 bar*	G.1/4" 4 VIE *G.1/4" 4-WAY*	Standard EURO con terminali a vite *EURO-Standard with screw terminals*	EV S attacco rapido 6mm *EV S quick connect 6mm*	PG 13,5 Z con gommino + PG 13,5 ZK con gommino e supporto cavo *PG 13.5 Z with strain relief + PG 13.5 ZK with strain relief and cable support*	Termica 6,3-10 A *Overload relay 6.3-10 A*	Diaframma standard, pulsante ON/OFF *Standard diaphragm, ON-OFF manual switch*	
	127/5CT 10-16	**MDR 3** ***3-phase***	11 bar	Pre-tarato a 7-9 bar *Pre-adjusted at 7-9 bar*	G.1/4" 4 VIE *G.1/4" 4-WAY*	Standard EURO con terminali a vite *EURO-Standard with screw terminals*	EV S attacco rapido 6mm *EV S quick connect 6mm*	PG 13,5 Z con gommino + PG 13,5 ZK con gommino e supporto cavo *PG 13.5 Z with strain relief + PG 13.5 ZK with strain relief and cable support*	Termica 10,0-16,0 A *Overload relay 10.0-16.0 A*	Diaframma standard, pulsante ON/OFF *Standard diaphragm, ON-OFF manual switch*	
	127/5CT 16-20	**MDR 3** ***3-phase***	11 bar	Pre-tarato a 7-9 bar *Pre-adjusted at 7-9 bar*	G.1/4" 4 VIE *G.1/4" 4-WAY*	Standard EURO con terminali a vite *EURO-Standard with screw terminals*	EV S attacco rapido 6mm *EV S quick connect 6mm*	PG 13,5 Z con gommino + PG 13,5 ZK con gommino e supporto cavo *PG 13.5 Z with strain relief + PG 13.5 ZK with strain relief and cable support*	Termica 16,0-20,0 A *Overload relay 16.0-20.0 A*	Diaframma standard, pulsante ON/OFF *Standard diaphragm, ON-OFF manual switch*	

PRESSOSTATI PER COMPRESSORI ARIA
PRESSURE SWITCHES FOR AIR COMPRESSORS

	Ref.	**Modello** ***Model***	Monofase/ Trifase *Single phase / Triphase*	Contatti *Contacts*	Pressione *Pressure*	Taratura di fabbrica *Factory pressure adjustment*	Flangia *Flange*	Valvola di scarico *Unloader valve*	Altre caratteristiche *Other details*	€
					NE-MA					
	126/3N	**MIGNON PM**	MONOFASE *SINGLEPHASE*	BIPOLARE *2 POLES*	4 ÷ 12 BAR	Pre-tarato a 6 ÷ 8 bar *Pre-adjusted at 6 ÷ 8 bar*	FLANGIA G1/4" 1 VIA *FLANGE G1/4" 1 WAY*	VRP attacco rapido 6mm chiusura a 1,4 bar *VRP quick connect 6mm delayed at 1,4 bar*	Differenziale fisso -2 bar, pulsante ON/OFF *Fixed differential -2 bar, ON-OFF manual switch*	
	126/4N	**MIGNON PM**	MONOFASE *SINGLEPHASE*	BIPOLARE *2 POLES*	4 ÷ 12 BAR	Pre-tarato a 6 ÷ 8 bar *Pre-adjusted at 6 ÷ 8 bar*	FLANGIA G1/4" 4 VIE *FLANGE G1/4" 4 WAYS*	VRP attacco rapido 6mm chiusura a 1,4 bar *VRP quick connect 6mm delayed at 1,4 bar*	Differenziale fisso -2 bar, pulsante ON/OFF *Fixed differential -2 bar, ON-OFF manual switch*	
	126/5N	**MIGNON PM**	MONOFASE *SINGLEPHASE*	BIPOLARE *2 POLES*	4 ÷ 12 BAR	Pre-tarato a 8 ÷ 10 bar *Pre-adjusted at 8 ÷ 10 bar*	FLANGIA G1/4" 1 VIA *FLANGE G1/4" 1 WAY*	VRO ottone a ogiva 6mm chiusura a 1,4 bar *VRO brass screw fixing 6mm delayed at 1,4 bar*	Differenziale fisso -2 bar, pulsante ON/OFF *Fixed differential -2 bar, ON-OFF manual switch*	
	126/7N	**MIGNON PM**	MONOFASE *SINGLEPHASE*	BIPOLARE *2 POLES*	4 ÷ 12 BAR	Pre-tarato a 6 ÷ 8 bar *Pre-adjusted at 6 ÷ 8 bar*	FLANGIA G1/4" 4 VIE *FLANGE G1/4" 4 WAYS*	VRO ottone a ogiva 6mm chiusura a 1,4 bar *VRO brass screw fixing 6mm delayed at 1,4 bar*	Differenziale fisso -2 bar, pulsante ON/OFF *Fixed differential -2 bar, ON-OFF manual switch*	
	126/6N	**MIGNON PM**	MONOFASE *SINGLEPHASE*	BIPOLARE *2 POLES*	4 ÷ 12 BAR	Pre-tarato a 6 ÷ 8 bar *Pre-adjusted at 6 ÷ 8 bar*	FLANGIA G1/4" 4 VIE *FLANGE G1/4" 4 WAYS*	VNP attacco rapido 6mm normalmente chiusura *VNP quick connect 6mm normally closed*	Differenziale fisso -2 bar, pulsante ON/OFF *Fixed differential -2 bar, ON-OFF manual switch*	
	126/1N	**EXPORT SPECIAL PES12**	TRIFASE *3-PHASE*	TRIPOLARE *3 POLES*	2,5 ÷ 12 BAR	Pre-tarato a 6 ÷ 8 bar *Pre-adjusted at 6 ÷ 8 bar*	FLANGIA G1/4" 1 VIA *FLANGE G1/4" 1 WAY*	in ottone ad ogiva per tubo rilsan o rame d.6 mm, normalmente chiusa *brass, screw fitting for plastic or copper pipe 6 mm, normally closed*	Differenziale regolabile min 2 bar, max 4,5 bar, pulsante ON/OFF *Adjustable differential min 2 bar, max 4.5 bar ON-OFF manual switch*	
	126/2N	**EXPORT SPECIAL PES12**	TRIFASE *3-PHASE*	TRIPOLARE *3 POLES*	2,5 ÷ 12 BAR	Pre-tarato a 6 ÷ 8 bar *Pre-adjusted at 6 ÷ 8 bar*	FLANGIA G1/4" 4 VIE *FLANGE G1/4" 4 WAYS*	in ottone ad ogiva per tubo rilsan o rame d.6 mm, normalmente chiusa *brass, screw fitting for plastic or copper pipe 6 mm, normally closed*	Differenziale regolabile min 2 bar, max 4,5 bar, pulsante ON/OFF *Adjustable differential min 2 bar, max 4.5 bar ON-OFF manual switch*	

PRESSOSTATI PER COMPRESSORI ARIA
PRESSURE SWITCHES FOR AIR COMPRESSORS

	Ref.	**Modello** ***Model***	Monofase/ Trifase *Single phase / Triphase*	Contatti *Contacts*	Pressione *Pressure*	Taratura di fabbrica *Factory pressure adjustment*	Flangia *Flange*	Valvola di scarico *Unloader valve*	Altre caratteristiche *Other details*	€
					NE-MA					
	126/5NT	**EXPORT THERM1 ET12**	TRIFASE *3-PHASE*	TRIPOLARE *3 POLES*	4 ÷ 12 BAR	Pre-tarato a 8 ÷ 10 bar *Pre-adjusted at 8 ÷ 10 bar*	FLANGIA G1/4" 4 VIE *FLANGE G1/4" 4 WAYS*	in ottone normalmente chiusa + raccordo L attacco rapido 6mm *brass, normally closed + 6 mm elbow push-in fitting*	Differenziale regolabile min 2 bar, max 4,5 bar pulsante ON/OFF Termica 6,3-10 A *Adjustable differential min 2 bar, max 4.5 bar ON-OFF manual switch Overload relay 6,3-10 A*	
	126/6NT	**EXPORT THERM2 ET2**	TRIFASE *3-PHASE*	TRIPOLARE *3 POLES*	4 ÷ 12 BAR	Pre-tarato a 8 ÷ 10 bar *Pre-adjusted at 8 ÷ 10 bar*	FLANGIA G1/4" 4 VIE *FLANGE G1/4" 4 WAYS*	in ottone ad ogiva per tubo rilsan o rame d.6 mm, normalmente chiusa *brass, screw fitting for plastic or copper pipe 6 mm, normally closed*	Differenziale regolabile min 2 bar, max 4,5 bar pulsante ON/OFF Termica 6,3-10 A *Adjustable differential min 2 bar, max 4.5 bar ON-OFF manual switch Overload relay 6,3-10 A*	
	126/7NT	**EXPORT THERM2 ET2**	TRIFASE *3-PHASE*	TRIPOLARE *3 POLES*	4 ÷ 12 BAR	Pre-tarato a 8 ÷ 10 bar *Pre-adjusted at 8 ÷ 10 bar*	FLANGIA G3/8" 4 VIE *FLANGE G3/8" 4 WAYS*	in ottone ad ogiva per tubo rilsan o rame d.6 mm, normalmente chiusa *brass, screw fitting for plastic or copper pipe 6 mm, normally closed*	Differenziale regolabile min 2 bar, max 4,5 bar pulsante ON/OFF Termica 6,3-10 A *Adjustable differential min 2 bar, max 4.5 bar ON-OFF manual switch Overload relay 6,3-10 A*	
	126/8N	**EXPORT THERM1 ET12**	TRIFASE *3-PHASE*	TRIPOLARE *3 POLES*	7,3 ÷ 16 BAR	Pre-tarato a 6 ÷ 8 bar *Pre-adjusted at 6 ÷ 8 bar*	FLANGIA G1/4" 4 VIE *FLANGE G1/4" 4 WAYS*	in ottone ad ogiva per tubo rilsan o rame d.6 mm, normalmente chiusa *brass, screw fitting for plastic or copper pipe 6 mm, normally closed*	Differenziale regolabile min 3 bar, max 4,5 bar pulsante ON/OFF Termica 6,3-10 A *Adjustable differential min 3 bar, max 4.5 bar ON-OFF manual switch Overload relay 6,3-10 A*	