SUPERMONDIAL/20



Descrizione Description		PEs. Bar Working Press. bar	P Scoppio Bar Bursting Press. bar	Peso nom. kg/m Weight kg/m	UM		
TUBO G SUPERMONDIAL/20	6X14	20	60	0,17	mt.	100	100
TUBO G SUPERMONDIAL/20	8X17	20	60	0,19	mt.	100	100
TUBO G SUPERMONDIAL/20	10X19	20	60	0,28	mt.	100	100
TUBO G SUPERMONDIAL/20	13X23	20	60	0,38	mt.	100	100
TUBO G SUPERMONDIAL/20	16X26	20	60	0,43	mt.	100	100
TUBO G SUPERMONDIAL/20	19X30	20	60	0,57	mt.	50	50
TUBO G SUPERMONDIAL/20	25X37	20	60	0,77	mt.	50	50

I VALORI RIPORTATI SONO RIFERITI AD UNA TEMPERATURA DI +18°C | THE DATA ARE REFERRED TO A TEMPERATURE OF +18°C

IT|

Tubo long lenght per mandata di acqua industriale, aria e fluidi non corrosivi. Sottostrato nero liscio in elastomero TIPRENE con ottime caratteristiche meccaniche e bassa permeabilità all'aria, rete di fili poliestere ad alta tenacità, copertura in elastomero TIPRENE resistente all'abrasione ed all'invecchiamento. Superficie esterna nera liscia. Temperatura di esercizio -30+60°C. Altre dimensioni lunghezze e colori sono realizzabili su richiesta.

Tolleranze: ISO 1307.

EN|

For compressed air, water and non corrosive fluids delivery. Black, smooth TIPRENE elastomer inner layer with great mechanical features, air tight. Polyester yarn reinforcement. Black, smooth TIPRENE elastomer outer layer abrasion and ageing resistant. Long length construction. Temperature range: -30°C to +60°C. Other dimensions, lengths, colors and pressures available on request.

Tolerances: According to ISO 1307.