RUBINETTI RAPIDI – DI SICUREZZA A BOTTONE
QUICK COUPLINGS – WITH BUTTON SAFETY

Caratteristiche tecniche: Linea di raccordi di sicurezza a bottone, con corpo rotante antigraffio e antiurto. Sono conformi alla normativa ISO 4414. Il corpo è in alluminio rivestito in morbida plastica che garantiscono al rubinetto robustezza, affidabilità e resistenza agli impatti. Il sistema di sgancio a bottone permette, con due semplici pressioni, di sostituire rapidamente l'utensile collegato all'alimentazione. La prima pressione consente di scaricare l'aria in pressione all'interno dell'utensile, la seconda pressione di scollegare in assoluta sicurezza l'apparecchiatura dal rubinetto.

Technical features: *Line safety couplings with button, with scratchproof and shockproof rotating body. They comply to ISO 4414 regulation. The body is made of aluminium and covered with soft plastic, which give the couplings hardness, reliability and impact strength. The button release device enables to replace quickly the air tool connected to power by simply pushing the button twice: the first time the button is pushed, the pressurized air inside the tool is released; the second time the button is pushed, the air tool is totally safely disconnected from the coupling.*

FILETTO CON O-RING • THREAD WITH O-RING
ROTAZIONE LIBERA A 360° • *360° FREE ROTATION*
CORPO IN GOMMA ANTIGRAFFIO E ANTIURTO • *SCRATCH- AND SHOCK-PROOF RUBBER BODY*

Temperatura di esercizio: *Working temperature:* +70°C
Pressione • *Pressure:* 12 Bar



Compatibile con : *Compatible with :*



Maschio • *Male*



Femmina • *Female*



Art.	Size	€
SC/1	1/4"	
SC/2	3/8"	
SC/3	1/2"	
SC/A1	1/4"	
SC/A2	3/8"	
SC/A3	1/2"	

Attacco portagomma
With hose tail fitting



Attacco tubo gomma e PU
With connection for rubber and PU hose



Art.	Ø	€
SC/B1	6	
SC/B2	8	
SC/B3	9	
SC/B4	10	
SC/B5	13	
SC/D1	6 x 14	
SC/D2	8 x 17	
SC/D3	10 x 19	