RACCORDI A CALZAMENTO
PUSH-ON FITTINGS

INOX AISI 316

Caratteristiche tecniche: Corpo in **ACCIAIO INOX 316**. Sono particolarmente adatti negli assemblaggi di tubi "plastici", in particolar modo dove possono esserci vibrazioni o condizioni climatiche estreme. Campi di impiego: aria compressa, alimentare, chimico, medicale. Tubi di collegamento: tubi plastici (Nylon - Polietilene - Poliuretano - Teflon). La pressione massima di esercizio e la temperatura sono determinate dalle caratteristiche del tubo impiegato. Pressione massima consigliata: 25 Bar. Temperatura di utilizzo: -40°C +180°C, -20°C +120°C (raccordi girevoli). Filettatura: Gas conica ISO 7 - DIN 2999. Gas cilindrica ISO 228. Metrica - ISO R/262.

Technical features *: **STAINLESS STEEL AISI 316** body. They are mainly used in "plastic" hoses assemblies especially in case of vibrations or extreme climatic conditions. Fields of application: compressed air, food, chemical, medical industry. Connecting tubes: plastic hoses (Nylon - Polyethylene - Polyurethane - Teflon). The working pressure and working temperature depend on which type of tube is used. Max pressure suggested: 25 Bar. Working temperature: -40°C + 180°C, -20°C +120°C (swivel fittings). Threads: Tapered gas ISO 7 - DIN 2999. Parallel gas ISO 228. Metric ISO R/262.*

	Art.	Size • Øe	€
Fisso diritto conico *Fixed straight tapered* 	640/1	1/8" 6	
	640/2	1/8" 8	
	640/3	1/4" 6	
	640/4	1/4" 8	
	640/5	1/4" 10	
	640/6	3/8" 10	
Intermedio diritto *Intermediate straight* 	641/1	6	
	641/2	8	
	641/3	10	
	641/4	12	
Fisso "L" conico *Fixed elbow tapered* 	642/1	1/8" 6	
	642/2	1/8" 8	
	642/3	1/4" 6	
	642/4	1/4" 8	
	642/5	1/4" 10	
Intermedio "T" *Intermediate tee* 	643/1	6	
	643/2	8	
	643/3	10	
	643/4	12	

	Art.	Size • Øe	€
Intermedio "L" *Intermediate elbow* 	644/1	6	
	644/2	8	
	644/3	10	
	644/4	12	
Fisso "T" centrale conico *Fixed central tapered tee* 	645/1	1/8" 6	
	645/2	1/8" 8	
	645/3	1/4" 6	
	645/4	1/4" 8	
	645/5	1/4" 10	
Fisso "T" laterale conico *Fixed lateral tapered tee* 	646/1	1/8" 6	
	646/2	1/8" 8	
	646/3	1/4" 6	
	646/4	1/4" 8	
	646/5	1/4" 10	
Dado bloccaggio *Blocking nut* 	647/1	6	
	647/2	8	
	647/3	10	