RACCORDI A COMPRESSIONE
COMPRESSION FITTINGS

Caratteristiche tecniche: Campi di impiego: circuiti pneumatici, oleodinamici e idraulici. Tubi di collegamento: tubi metallici (Rame - Ottone - Alluminio, ecc.) e con rinforzo interno (vedere ns. articolo 611) tubi plastici (Rilsan - Nylon - Poliuretano, ecc.). La pressione massima di esercizio e la temperatura sono determinate dalle caratteristiche del tubo impiegato. Pressione massima consigliata: 60 Bar. Trattamento superficiale: Nichelatura. Materiali impiegati: Ottone UNI EN 12164 CW 614N. Ottone UNI EN 12165 CW 617N. Filettatura Gas conica ISO 7 - DIN 2999 - BS 21. Gas cilindrica ISO 228.

Technical features: *Fields of application: pneumatic and hydraulic systems. Connecting tubes: for metal pipes (Copper - Brass - Aluminium, etc.) and internally reinforced plastic pipes (Rilsan - Nylon - Polyurethane, etc.) (see our item 611). The working pressure and working temperature depend on which type of tube is used. Max pressure suggested: 60 Bar. Surface treatment: Nickel-plating. Material used: Brass UNI EN 12164 CW 614N. Brass UNI EN 12165 CW 617N. Threads: Tapered gas ISO 7 - DIN 2999 - BS21. Parallel gas ISO 228.*

Fisso diritto conico
Fixed straight tapered



Art.	Size • Øe		€
350/0	1/8"	4	
350/1	1/8"	6	
350/1A	1/8"	7	
350/2	1/8"	8	
350/2A	1/4"	4	
350/3	1/4"	6	
350/4	1/4"	8	
350/5	1/4"	10	
350/5A	1/4"	12	
350/6	3/8"	8	
350/7	3/8"	10	
350/8	3/8"	12	
350/9	1/2"	10	
350/9A	1/2"	12	
350/10	1/2"	14	
350/11	1/2"	15	
350/12	1/2"	16	
350/13	1/2"	18	

Diritto femmina
Straight female



Art.	Size • Øe		€
358/1	1/8"	4	
358/2	1/8"	6	
358/3	1/8"	8	
358/4	1/4"	6	
358/5	1/4"	8	
358/6	1/4"	10	
358/7	3/8"	8	
358/8	3/8"	10	
358/9	1/2"	10	
358/12	1/2"	15	
358/14	1/2"	18	

Fisso "L" conico
Fixed tapered elbow



Art.	Size • Øe		€
352/0	1/8"	4	
352/1	1/8"	6	
352/2	1/8"	8	
352/2A	1/4"	4	
352/3	1/4"	6	
352/4	1/4"	8	
352/5	1/4"	10	
352/6	3/8"	8	
352/7	3/8"	10	
352/8	3/8"	12	
352/8A	3/8"	14	
352/9	1/2"	10	
352/10	1/2"	12	
352/11	1/2"	14	
352/13	1/2"	15	
352/14	1/2"	16	
352/12	1/2"	18	

Fisso "L" femmina
Fixed female elbow



Art.	Size • Øe		€
357/1	1/8"	4	
357/2	1/8"	6	
357/3	1/8"	8	
357/4	1/4"	6	
357/5	1/4"	8	

Testina orientabile "L"
Elbow revolving head



Art.	Size • Øe		€
356/1	1/8"	4	
356/2	1/8"	6	
356/3	1/4"	6	
356/4	1/8"	8	
356/5	1/4"	8	

Intermedio diritto
Intermediate straight



Art.	Size • Øe		€
351/0	4		
351/1	6		
351/2	8		
351/3	10		
351/4	12		
351/5	14		
351/6	15		
351/7	16		
351/8	18		

Intermedio "L"
Intermediate elbow



Art.	Size • Øe		€
353/0	4		
353/1	6		
353/2	8		
353/3	10		
353/4	12		
353/5	14		
353/7	15		
353/8	16		
353/6	18		

Fisso "T" centrale conico
Fixed central tapered tee



Art.	Size • Øe		€
354/0	1/8"	4	
354/1	1/8"	6	
354/2	1/8"	8	
354/3	1/4"	6	
354/4	1/4"	8	
354/5	1/4"	10	
354/6	3/8"	8	
354/7	3/8"	10	
354/8	3/8"	12	
354/9	1/2"	12	
354/10	1/2"	14	
354/11	1/2"	16	

Intermedio "T"
Intermediate tee



Art.	Size • Øe		€
355/0	4		
355/1	6		
355/2	8		
355/3	10		
355/4	12		
355/5	14		
355/6	16		
355/7	18		

Ogiva di bloccaggio
Blocking bush



Art.	Size • Øe		€
360/0	4		
360/1	6		
360/2	8		
360/3	10		
360/4	12		
360/5	14		
360/6	15		
360/7	16		
360/8	18		

Bussola di rinforzo
Reinforcing bush



Art.	Size • Øe		€
611/0B	4 x 2		
611/0	4 x 2,5		
611/0A	6 x 4		
611	8 x 6		
611/1	10 x 8		
611/2	12 x 10		
611/2A	14 x 12		
611/3	15 x 12		
611/3A	16 x 14		
611/4	18 x 15		